

Phone: 02 67425588

Email: sales@chaffeys.com.au

Website: https://www.chaffeys.com.au

31-33 Bloomfield St Gunnedah NSW 2380



Honda UMK425 Loop Handle Brushcutter

Specifications

Boat Details

Price POA Boat Brand Honda

Model UMK425 Loop Handle Brushcutter Length 0.00

Year 2022 Category Brushcutters

Hull StyleHull TypePower TypeStock Number

Condition New State New South Wales

Suburb GUNNEDAH Engine Make

Disclaimer



Phone: 02 67425588

Email: sales@chaffeys.com.au

Website: https://www.chaffeys.com.au

31-33 Bloomfield St Gunnedah NSW 2380

Description

Boasting the latest in Honda's ultra-compact, lightweight, 4-Stroke engines, Honda's UMK425 Loop Brushcutteroffers superb power and more torque than ever before.

Honda leads the world with revolutionary mini 4-Stroke engines that deliver more power and use less oil than 2-stroke alternatives. TheUMK425 Loopis powered by Honda's new Generation II GX25 Mini 4-Stroke engine delivering commercial-grade power.

And with its auto-decompression, electronic ignition and anti-flood primer system, the UMK425 Loopwill start first time, every time, year after year. It's what you've come to expect from Honda. No More Mixing

TheUMK425 Loop Brushcutterruns on unleaded fuel, so you'll never get your hands dirty having to mix oil and petrol again just to get the thing going!

Superior engineering means the UMK425 Loopwill produce less noise and smoke, making it environmentally friendly - and easy on your body.

And you'll save money on 2-Stroke oil, compared to competitors. Especially relevant to commercial operators, why wouldn't you want a product that maximises your profits? Honda Technology

TheUMK425 Loop Brushcutterfeatures full 360° "any-side-up" operation, so you can use and store it in any position.

It delivers excellent torque and performance via an all-new Generation II, GX25 4-Stroke engine.

And user comfort is uncompromised too, with the UMK425 Loop handle featuring a comfortable solid drive shaft with unique anti-vibration engine mount. Specifications

ENGINE ∏∏GX25

DISPLACEMENT [][]25cc

BORE AND STROKE □□□35 x 26mm

MAXIMUM POWER OUTPUT □□□0.81W (1.1hp) @ 7000rpm

MAXIMUM TORQUE OUTPUT [][]1.25N.m @ 5000rpm

LUBRICATION SYSTEM □□□Rotary Type (oil mist)

OIL CAPACITY (LITRES) ∏∏0.08 litres

FUEL TANK CAPACITY (LITRES) □□□0.55 litres

FUEL TYPE ∏∏∏Unleaded

DIMENSIONS (LxWxH) $\square \square \square 1,835 \times 325 \times 240 \text{ (mm)}$

DRY WEIGHT ∏∏5.7 kg (without cutting head)

BLADE [[[]Optional extra

ANTI-VIBRATION □□□Yes

GUARDS □□□1

GOGGLES ∏∏∏Yes

HARNESS Desired Operator Harness

HANDLE TYPE □□□Loop

DRIVE SHAFT DDDSolid

Disclaimer