



Honda VersaTool 25cc Power Head

POA

Specifications

Boat Details

Price	POA	Boat Brand	Honda
Model	VersaTool 25cc Power Head	Length	0.00
Year	2022	Category	Boat Parts and Accessories
Hull Style		Hull Type	
Power Type		Stock Number	
Condition	New	State	New South Wales
Suburb	GUNNEDAH	Engine Make	

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.

Description

Powered by Honda's famous 25cc 4-Stroke Engine, this VersaTool powerhead already comes standard on most of Honda's range of handheld power equipment suitable for the residential user, this powerhead delivers the 'starts-first-time every-time' reliability that Honda is known for, and offers superior performance no matter what attachment is connected. A lightweight and ergonomic design, paired with the power that comes standard with a Honda, results in a power source that you can rely on day in, day out. Advanced Technology

The world's lightest OHC engine, the Honda Mini 4-stroke engine requires no fuel/oil mixing, and runs at approximately half the operating cost of comparable 2-stroke engines. A full 360° "any-side-up" operation means you can use and store the UMC425 in any position, and take advantage of the exclusive rotary-slinger lubrication system. The carburetor is equipped with an accelerator pump for fast, easy acceleration, and an efficient port configuration and large diameter valves maximise power output. Specifications

MODEL UMC425

VERSATOOL COMPATIBLE Yes

TYPE 4-stroke, overhead cam, single-cylinder, horizontal shaft

BORE & STROKE 35 x 26 mm (1.4 x 1.0 in)

DISPLACEMENT 25cm³ (1.5 cu in)

COMPRESSION RATIO 8.0:1

NET POWER 0.72kW (1.0HP) at 7,000 rpm

MAXIMUM NET TORQUE 1.0 Nm (0.74 lbs ft) at 5,000 rpm

IGNITION SYSTEM Transistorised magneto ignition

STARTING SYSTEM Recoil Starter

COOLING SYSTEM Forced-air

PTO SHAFT ROTATION Counter-clockwise (from P.T.O. side)

FUEL CONSUMPTION AT RATED POWER 0.54 L/h at 7,000 rpm

RECOMMENDED FUEL Unleaded

LUBRICATION SYSTEM Oil Mist

OIL CAPACITY 0.08l

FUEL TANK CAPACITY 0.55l

DIMENSIONS 192mm x 221mm x 230mm

DRY WEIGHT 2.78kg (w/o clutch)

OTHER SPECS Infinite Operating Angles

PRICE \$539

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.